

OPERATION

os inside the watchcase, ask nbly and repair atonce, or sed by corrosion.
electronic forms can be gravity suffered the impact the Button

or high cycle

zing environment.

th and clear watch, don't its own characteristics, limate The table in use for colors may be subject to all category).

(LIGHT/SET)

But t on

explain

lease place it in a dry place.
arefully before using this watch.
e in order to prevail in kind

SPECIFICATION

C (ADJUST)--A (MODE)

O HOW TO CHANGE 12/24 FOR In normal display press C button. CORMAL DISPLAY
(24H FORMAT) FORMAT ORMAL DISPLAY
(12H FORMAT)

Use tempearature: 5°C-35°C
 Degree of accuracy at normal temperature: 60second one month
 Battery: CR2016 3V
 LIfe of battery: able to supply powerfor 18 months under the following situation:
 One illumination per day
 One alarm operation per day

NORMAL DISPL

MANUFACTURERS: SHENZHEN YAOJINRONG TECHNOLOGY CO., LTD ADDRESS: HUAFENG SCIENCE PARK, BAO'AN, SHENZHEN, GUANGDONG, CHINA TEL:0086-0755-29563563

http://yaojinrong.en.alibaba.com/

O HOW TO USE LIGHT

In any display mode press B button lit LED lights. Press and hold down the colored lights can be continuously synchronized output ALARM ON/OFF and 12/24 forming can change every digit button Normal display ction selct button sketch map O HOW \bigcirc when min adjust m HOW ALARM



